

Draadvormende schroeven in staal

Maat	Gat Diameter voor				Draad Diameter			
	Gieten							
	A - Top		B - Bodem		C		D	
	Max.	Min.	Max.	Min.	Max.	Min.	Max.	Min.
M2 x 0.40	1.91	1.83	1.81	1.73	2,06	2,00	1,98	1,92
M2.5x0.45	2.39	2.31	2.28	2.20	2,57	2,50	2,48	2,41
M3x0.5	2.90	2.82	2.76	2.68	3,07	3,00	2,97	2,90
M3.5x0.6	3.31	3.23	3.21	3.13	3,58	3,50	3,46	3,38
M4x0.7	3.82	3.74	3.64	3.56	4,08	4,00	3,94	3,86
M5x0.8	4.8	4.72	4.58	4.50	5,09	5,00	4,93	4,84
M6x1.0	5.75	5.66	5.48	5.40	6,10	6,00	5,9	5,80
M8x1.25	7.69	7.61	7.32	7.27	8,13	8,00	7,88	7,75
M10x1.5	9.64	9.56	9.22	9.14	10,15	10,00	9,85	9,70
			Boordiam.					
Mat.dikte	0,5-2	1,5-3,5	3-6,5	6-8	8-12			
M2 x 0.40	1,75	1,80						
M2.5x0.45	2,25	2,30	2,35					
M3x0.5	2,70	2,75	2,80					
M3.5x0.6	3,10	3,20	3,20	3,25	3,30			
M4x0.7	3,60	3,70	3,75	3,75	3,80			
M5x0.8		4,50	4,60	4,70	4,70			
M6x1.0		5,40	5,50	5,60	5,70			
M8x1.25		7,30	7,40	7,50	7,60			
M10x1.5			9,25	9,30	9,40			
Lengte	Tol.	F	L	H min.	J min.			
5 mm	0,25	1.81	4.00	3.32	1.04			
6 mm	0,25	2.28	5.00	4.15	0.55			
8 mm	0,30	2.76	6.00	4.98	0.61			
10 mm	0,30	3.21	7.00	5.81	0.74			
12 mm	0,35	3.64	8.0	6.64	0.86			
16 mm	0,35	4.58	10.00	8.30	.098			
20 mm	0,40	5.48	12.00	9.96	1.23			
25 mm	0,40	7.35	16.00	13.28	1.53			
30 mm	0,40	9.22	20.00	16.60	1.84			